



MDM Model Identification Guide

MDM	1518	EKK	05	H
	1	2	3	4

1. Pump Size

Model	Suction	Discharge	Motor HP	Motor Frame
1516*	1 ½	1	2	145TC, FOOTLESS
1516*			3	182TC, FOOTLESS
1518*			5	184TC, FOOTLESS
1518*			7.5	213TC, W/FEET
1518*			10	215TC, W/FEET
1518-2			7.5	213TC, W/FEET
1518-2			10	215TC, W/FEET
1518-2			15	254TC, W/FEET
1518-2			20	256TC, W/FEET
1518-2			25	284TSC, W/FEET
2156			2	1 ½
2156	7.5	213TC, W/FEET		
2156	10	215TC, W/FEET		
2158	7.5	213TC, W/FEET		
2158	10	215TC, W/FEET		
2158	15	254TC, W/FEET		
2158	20	256TC, W/FEET		
2158	25	284TSC, W/FEET		
2526	2 ½	2	5	184TC, FOOTLESS
2526			7.5	213TC, W/FEET
2526			10	215TC, W/FEET
326*	3	2	7.5	213TC, W/FEET
326*			10	215TC, W/FEET
326*			15	254TC, W/FEET
326*			20	256TC, W/FEET
326*			25	284TSC, W/FEET

* Denotes ANSI standard dimensional unit.

2. Liquid End Construction

Bearing option	ECF*	EKK	PKK
Casing Liner/Containment Shell	20% carbon fiber reinforced copolymer ETFE		PFA
Impeller			
Inner Magnet			
Radial bearing	High Density Carbon	SiC	
Shaft	99.8% alumina ceramic		
Front Outboard Thrust Collar	99.8% alumina ceramic		
Front Inboard Thrust Collar	PTFE (w/filler)		
Rear Inboard Thrust Collar	99.8% alumina ceramic		
Rear Outboard Thrust Collar	PTFE (w/filler)		PTFE
Casing Gasket	PTFE		

* Dry run capable configuration

3. Motor Size

02, 03, 05, 07, 10, 15, 20, 25	2 HP through 25 HP
--------------------------------	--------------------

4. H = High Temperature Version

(only available on 1518-2 and 2158 models)